



Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Outside width of lower ladder: 420 mm.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Product features

Coating: natural

Connection between stiles and rungs/stiles: flanged

External width of lower ladder: 420 mm

Load: max. 150 kg

Material: aluminium

Product type: Flanged push-up ladder with rungs, 2 sections

Tread depth: 38 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 265 mm

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44834	8	2 × 8	3.8 m	2.42 m	58 mm	2.420 mm × 420 mm × 115 mm	9.3 kg	0.8 m	4.6 m
44820	10	2 × 10	4.93 m	2.98 m	68 mm	2.980 mm × 430 mm × 120 mm	11.3 kg	0.9 m	5.65 m
44822	12	2 × 12	6.05 m	3.54 m	68 mm	3.540 mm × 430 mm × 135 mm	15.4 kg	1 m	6.8 m
44824	14	2 × 14	7.17 m	4.1 m	85 mm	4.100 mm × 430 mm × 135 mm	17.8 kg	1.1 m	7.85 m
44826	16	2 × 16	8.29 m	4.66 m	85 mm	4.660 mm × 430 mm × 145 mm	21.5 kg	1.2 m	8.7 m



Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44828	18	2 × 18	9.17 m	5.23 m	85 mm	5.230 mm × 430 mm × 145 mm	23.9 kg	1.2 m	9.8 m