


# XLstep S

Light weight and easy to handle, as well as great value.

## Product description

- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon straps prevent splay, from 4 treads.
- Triple-riveted connection between rung and stile.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



## Product features

Anti-splay mechanism: Belt strap  
 Coating: anodised  
 Connection between stiles and rungs/stiles: riveted  
 Length as work platform: 250 mm  
 Load: max. 150 kg  
 Material: aluminium  
 Platform width: 300 mm  
 Product type: Riveted stepladder with treads  
 Stile depth: 42 mm  
 Storage tray: aluminium  
 Tread depth: 80 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 250 mm

## Hints and special features

Complies with EN 131 Professional.

## Product variants

| Order number | Base            | Number of rungs, incl. platform | Overall base width | Overall length | Platform height | Stile depth | Stile depth steps/back stay | Transport dimensions                               | Vertical ladder height | Weight  | Working height |
|--------------|-----------------|---------------------------------|--------------------|----------------|-----------------|-------------|-----------------------------|----------------------------------------------------|------------------------|---------|----------------|
| 41223        | 0,74 m × 0,49 m | 3                               | 0.49 m             | 1.56 m         | 0.74 m          | 42 mm       | 42mm / 42mm                 | approx. 1.560 mm × approx. 490 mm × approx. 155 mm | 1.42 m                 | 6 kg    | 2.75 m         |
| 41224        | 0,91 m × 0,52 m | 4                               | 0.52 m             | 1.83 m         | 0.99 m          | 42 mm       | 42mm / 42mm                 | approx. 1.830 mm × approx. 520 mm × approx. 155 mm | 1.67 m                 | 6.9 kg  | 3 m            |
| 41225        | 1,08 m × 0,55 m | 5                               | 0.55 m             | 2.1 m          | 1.24 m          | 42 mm       | 42mm / 42mm                 | approx. 2.100 mm × approx. 550 mm × approx. 155 mm | 1.92 m                 | 7.7 kg  | 3.25 m         |
| 41226        | 1,25 m × 0,57 m | 6                               | 0.57 m             | 2.37 m         | 1.49 m          | 48 mm       | 48mm / 42mm                 | approx. 2.370 mm × approx. 570 mm × approx. 155 mm | 2.17 m                 | 9.1 kg  | 3.5 m          |
| 41227        | 1,42 m × 0,61 m | 7                               | 0.61 m             | 2.64 m         | 1.74 m          | 48 mm       | 48mm / 42mm                 | approx. 2.640 mm × approx. 610 mm × approx. 155 mm | 2.42 m                 | 10.2 kg | 3.75 m         |



| Order number | Base               | Number of rungs, incl. platform | Overall base width | Overall length | Platform height | Stile depth | Stile depth steps/back stay | Transport dimensions                                     | Vertical ladder height | Weight  | Working height |
|--------------|--------------------|---------------------------------|--------------------|----------------|-----------------|-------------|-----------------------------|----------------------------------------------------------|------------------------|---------|----------------|
| 41228        | 1,59 m<br>× 0,63 m | 8                               | 0.63 m             | 2.91 m         | 1.99 m          | 48 mm       | 48mm / 42mm                 | approx. 2.910 mm ×<br>approx. 630 mm ×<br>approx. 155 mm | 2.67 m                 | 11.7 kg | 4 m            |
| 41230        | 1,93 m<br>× 0,69 m | 10                              | 0.69 m             | 3.45 m         | 2.49 m          | 48 mm       | 48mm / 42mm                 | approx. 3.450 mm ×<br>approx. 690 mm ×<br>approx. 155 mm | 3.17 m                 | 14.1 kg | 4.5 m          |